

## **Product information**

# Stuffing-Box-Packing Type 2127

### Description

Diagonally braided from synthetic fibre, impregnated throughout with PTFE-dispersion, lubricated with silicone oil.

#### **Properties**

Style 2127 is a dense, yet soft and pliable packing . The combination of the synthetic fibres, the PTFE-impregnation and the high-temperature break-in lubricant results in a packing with very low shaft wear and outstanding durability.

#### Application areas

Multi-purpose packing which can be used in pumps, mixers, kneaders and valves in the chemical, pharmaceutical, pulp- and paper and food industry.

#### Application media

TEADIT style 2127 covers a wide variety of media like water, steam, diluted acids and lyes, most chemicals, gases, etc.


#### Not suitable for

Concentrated acids and lyes, oxygen, lacquers and paint.

#### **Benefits**

Excellent all-round packing for many applications within a plant. Non contaminating, not shaft scouring.

WRAS approval for potable water



	. e te ti . g.		• • • • • •
(bar)	20	80	100

pH: 2-12 density: 1,35

v: (m/s) 12

#### Approval:

WRAS

Since all properties, specifications and application parameters shown throughout this catalogue are approximate and may be mutually influenced, your specific application should not be undertaken without independent study and evaluation for suitability. All technical data and advice given is based on experiences TEADIT® has made so far. Failure to select proper sealing products can result in damage and/or personal injury. Properties, specifications and application parameters are subject to change without notice. TEADIT® does not undertake any liability of any kind whatsoever. Please note: the color of the actual product might vary from the above image on this data-sheet.

REV2016152